


GTM-170/190



MENTEN

1.Tilt Angle 0°~90°
Adapt to operation in any environment.



2.Removable Base and Wall-Mounting capability with 75mm VESA holes

The GTM-170/190 series is a multi-functional Touch LCD Monitor specifically for retail & hospitality application such as hotels, restaurants and shops.

- Available with different touch panel technology.
- **■** (5-wire resistive, SAW, and Capacitive)
- With rugged and solid base design.
- User-Friendly manipulation.
- Choice of 17" and 19" TFT LCD Panel.
- Water Spill Resist from the front bezel side.
- OSD and Power Switch Control panel on the rear.
- With Dual VGA Interface. (VGA and DVI)
- With USB, RS-232, or Combo Touch Interface.
- Hidden Power Adapter Design.



3. Triple Track **Magnetic Stripe Reader** for membership management or operator identification



4.**Customer Display** (VFD type 2x20) can be integrated to the back side of the system



5.**Second display** can be integrated to the back side of the system



6.Easily arrange the cables inside the stand



## GTM-170/190

## **Specifications**

## **System**

| _ oystem          |  |                          |
|-------------------|--|--------------------------|
| Model Name        | GTM-170                                | GTM-190                  |
| Display Type      | Active Matrix TFT LCD                  |                          |
| Screen Size       | 17"                                    | 19"                      |
| Display Area (mm) | 338 (W) x 270 (H)                      | 376.32 (W) x 301.056 (H) |
| Max. Resolution   | 1280 x 1024                            | 1280 x 1024              |
| Colors            | 16.7 million                           |                          |
| Brightness        | 250~cd/m <sup>2</sup>                  | 250~cd/m²                |
|                   | (Typ.)                                 | (Typ.)                   |
| Contrast Ratio    | 450:1                                  | 550:1                    |
| Input Connector   | D-SUB 15 PIN Female / 24 PIN DVI       |                          |
| Power Supply      | 12V / 3A (External)                    | 12V / 4.3A (External)    |
| Color             | Black or Silver color                  |                          |
| Dimension (WxHxD) | 418 x 378 x 226 mm                     | 418 x 378 x 226 mm       |
| Temperature       | Operation: 0°C to 40°C                 |                          |
| Humidity          | 10% to 90%                             |                          |
| Touch Panel       | TW 5-wire or ELO Resistive Touch Panel |                          |
|                   | (RS-232, USB, or Combo)                |                          |
|                   | Capacitive ( RS-232 or USB )           |                          |
|                   | SAW ( RS-232 or USB )                  |                          |

## **Others**

**Optional Integrated Device** 

VFD Customer Display

MSR Card Reader

Second 8"/10"/12"/15"/17"/19" LCD Screen with or without Touch Screen

3-in-1 MSR + Smartcard + i-Button Reader

